

Our vibration finishing machines are suitable for trimming, blast cleaning, grinding and polishing of any parts made of steel, copper, aluminium or zinc based materials as well as of plastic, rubber and ceramic in various fields of the industry. These machines run with low operational cost and are featured by easy maintenance.

**With queries on repair and maintenance of the  
equipment, please contact: GRÁNIT-EX KFT**

**2657 Tolmács, Szent Lőrinc út 108. Tel: 06 35 350-631**

**granitexkft@gmail.com**

Technical data of our equipment:

Type	FM-1	FM-3 FM-2S	FM-10 FM-8S	FM-20 FM-16S	FM-40
Machine height	785	810	1105	1270	2064
Plate diameter	577	762	1270	1576	1896
Trough Width	203	260	343	500	600
Trough Depth	165	254	356	490	605
Plate capacity approx. litre	28	85	283	566	1133
Plate lining type	cast polyurethane	cast polyurethane	cast polyurethane	cast polyurethane	cast polyurethane
Electromotor output kW	0.17	0.525	2.4	3.6	5.8
Current drain A	0.60	0.92	3.90	6.70	11.8
Electromotor nominal rounds/min	1500	1500	1500	1500	1500
Voltage V	380/220	380/220	380/220	380/220	380/220
Frequency Hz	50	50	50	50	50
Calculated machine weight approx. kg	57	200	600	790	1500

Protection of the machine: IP 44

We do not stop working on updating our products; therefore, we reserve the right for changes in the technical data and structure of the machines.